



SORELEX INDUSTRIAL HOSES



SORELEX with its experience and know-how can offer the most extensive range of Industrial Hoses & Couplings. Continuous feedback, research and contact with the customers guarantee 100% satisfaction for each hose and each application. The rubber hoses are manufactured in two types depending on the manufacturing process i.e. extruded long length hose (up to 500meter) and mandrel built hose (up to 30.5meter) and with service ratio of 1:3 in compliance with BS, AS, DIN and EN standards. Depending on the application the industrial hoses can be broadly categorized into the following:

- **Air hose oil resistant 1/4" to 4" ID with maximum working pressure of 300 PSI**
- **Water Suction & Discharge Hose 3/4" to 12" ID in pressure rating of 150 PSI and 300 PSI**
- **Oil Suction & Discharge Hose 3/4" to 12" ID in pressure rating of 150 PSI and 300 PSI**
- **Multi Purpose Hose red colour 3/8" to 2" ID with working pressure of 300 PSI**
- **Bulk material Suction & Discharge Hose 2" to 8" ID with working pressure of 150 PSI**
- **LPG Hose 1/4" to 1" ID with working pressure of 150 PSI**
- **Sand Blast Hose 1/2" to 2" ID with working pressure of 150 PSI**
- **Potable Water Hose from 1/2" to 2" ID with working pressure of 150 PSI and material in compliance to FDA**
- **Steam Hose 1/4" to 2" ID with working pressure of 17 Bar and temperature 225° C**
- **PVC Hose fabric and wire reinforced up to 4" ID**



The hoses can be supplied with various types of couplings like Cam and Groove, Dry Quick Disconnect, Air Fittings, Shank and custom built in both field attachment and swaged type.

If assemblies are required to have proof pressure test at 1.5 times the rated working pressure than we recommend that end fittings be attached by internal/external swaging.